

WE CLAIM:

1. A fluorescence detector comprising:
 - a) a light source for exciting specific fluorophores located on a biopolymer array;
 - b) means for directing said light source into said waveguide support to cause total internal fluorescence in said waveguide support; and
 - c) a charge couple device for detecting emission spectra.
2. The fluorescence detector of claim 12, wherein said light source generates a laser beam.
3. The fluorescence detector of claim 12, wherein said light source generates multiple spectrally distinct laser beams.
4. The fluorescence detector of claim 12, wherein said light source is comprised of four spectrally distinct laser beams.
5. The fluorescence detector of claim 12, further comprising a transparent hexahedron, wherein said transparent hexahedron revolves around an axis perpendicular to said light beam for placing said light source into said waveguide support.
6. The fluorescence detector of claim 12, further comprising an optical wedge, wherein said optical wedge revolves around an axis approximating said light beam for placing said light source into said waveguide support.
7. The fluorescence detector of claim 12, further comprising a cylindrical lens for focusing said light beam into a shape smaller than an edge of said waveguide, wherein said light beam is entering said waveguide at said edge.
8. The fluorescence detector of claim 12, further comprising a mirror for directing said light beam into said waveguide support.
9. The fluorescence detector of claim 12, further comprising a diffraction grating for directing said light beam into said waveguide support.

10. The fluorescence detector of claim 12, further comprising an optical prism for directing said light beam into said waveguide support.

11. The fluorescence detector of claim 12, further comprising a transparent liquid placed between said waveguide support and said optical prism, wherein said transparent liquid possesses a refractive index about equal to the refractive indices possessed by said waveguide support and said optical prism.

12. The fluorescence detector of claim 12, wherein said waveguide support has a polished edge in which said light beam enters said waveguide support to illuminate said waveguide support broadly.

13. The fluorescence detector of claim 12, wherein said waveguide support has a frosted edge in which said light beam enters said waveguide support to illuminate said waveguide support broadly.

14. The fluorescence detector of claim 12, further comprising bandpass filters for separating emission spectra.

15. The fluorescence detector of claim 12, further comprising a personal computer to collect and analyze emission spectra.

00449604200

g and analyzing a sp
ide support into a flu
ed between a light so
n said waveguide su
least one said oligom
scintillant nucleotide by
from said fluorescen
ssion on a personal c

5

10

d) analyzing said emission on a personal computer.

0 0000 0000 0000 0000 0000 0000 0000 0000
1 0001 0001 0001 0001 0001 0001 0001 0001
2 0010 0010 0010 0010 0010 0010 0010 0010
3 0011 0011 0011 0011 0011 0011 0011 0011
4 0100 0100 0100 0100 0100 0100 0100 0100
5 0101 0101 0101 0101 0101 0101 0101 0101
6 0110 0110 0110 0110 0110 0110 0110 0110
7 0111 0111 0111 0111 0111 0111 0111 0111
8 1000 1000 1000 1000 1000 1000 1000 1000
9 1001 1001 1001 1001 1001 1001 1001 1001
A 1010 1010 1010 1010 1010 1010 1010 1010
B 1011 1011 1011 1011 1011 1011 1011 1011
C 1100 1100 1100 1100 1100 1100 1100 1100
D 1101 1101 1101 1101 1101 1101 1101 1101
E 1110 1110 1110 1110 1110 1110 1110 1110
F 1111 1111 1111 1111 1111 1111 1111 1111

ing the sequence of a p
of oligonucleotide pr
wherein said solid sup
lynucleotide of inter
gonucleotides;
able stranded oligonu
xtend the annealed pr
ide, wherein said prim
ide which is complim
ynucleotide of interes
port into a fluorescer
light source and a cha
source is able to speci
escent nucleotide by
n from said fluorescer
mission on a personal

- 20

Roll An

Add C2